

4-WHEEL SCOOTER

PATHRIDER 140 XL

ENGINEERED FOR
POWERFUL PERFORMANCE
AND EXCEPTIONAL STYLE

Bristling with high performance features like full suspension and a hydraulic sealed brake system, the **Pathrider® 140 XL** is a powerful blend of power and precision. The Pathrider 140 XL is equipped with sleek aggressive style and a wealth of standard luxury touches including a wraparound easy drive tiller and LED lighting, making it the ultimate outdoor scooter.



Full Suspension

PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

www.pridemobility.com.au

SPECIFICATIONS

PATHRIDER® 140 XL

4-wheel

Weight capacity:	181 kg (400 lbs.)
Maximum speed ¹ :	Up to 15 km/h (9.32 mph)
Ground clearance ² :	13.33 cm (5.25")
Turning radius ² :	Right: 210.8 cm (83"), Left: 208.3 cm (82")
Overall length ² :	142.8 cm (56.25")
Overall width ² :	69.2 cm (27.25")
Seat-to-floor height:	72.39 cm - 68.58 cm (28.5" - 27")
Front tyres:	10 cm x 33 cm (4" x 13") pneumatic
Rear tyres:	10 cm x 33 cm (4" x 13") pneumatic
Suspension:	Front and rear
Range per charge ^{1,4} :	Up to 35 km (21.70 miles) with 75 AH batteries Up to 46.57 km (28.94 miles) with 100 AH batteries
Total weight without batteries ^{2,5} :	117.70 kg (259.5 lbs.)
Heaviest piece when disassembled:	93.21 kg (205.5 lbs.) (main frame)
Standard seating:	Type: Pillow top deluxe high-back with sliders Weight: 21.77 kg (48 lbs.) Material: Black Vinyl Dimensions: 49.5 cm (19.5") width, 44.5 cm (17.5") depth
Drivetrain:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Brakes:	Regenerative and electromechanical
Battery requirements ³ :	(2) 12-volt, deep cycle Size: 100 AH or 75 AH Weight ⁶ : 100 AH: 27.44 kg (60.5 lbs.) each 75 AH: 25 kg (55 lbs.) each
Battery charger:	8 amp, off-board charger
Colours:	



Candy Apple Red



Yellow



Silver

- ¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+10%-5%).
- ² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- ³ AGM or gel cell type required.
- ⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- ⁵ Includes standard seat.
- ⁶ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

FEATURES

- Full suspension for optimum handling
- Sealed hydraulic brakes
- Large 33 cm (13") pneumatic tyres for excellent outdoor performance
- Full lighting package including directional signals and headlight
- Easy drive tiller with wraparound handles
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rearview mirror standard
- Front shield standard
- Pillow-top seat

OPTIONS

- Double crutch holder
- Oxygen tank holder
- Rear basket
- Additional rear view mirror



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®



(Tel) 03 8770 9600 • (Fax) 03 9703 2720

20-24 Apollo Drive Hallam, Victoria 3803

ACN 088 609 661 ABN 66 088 609 661

www.pridemobility.com.au

